

The Fiber Optic Tray KM 5 is designed to support up to 24 optical fibers and connectors. Fibers are terminated with pigtails to 12× SC or 24× LC connector – with additional PLC Splitter capacity. Splices are housed within the internal [Fiber Optic Tray KM 6](#). This allows for placing various types of Splice Holders. It is compatible with all types of fibers and is very intuitive to use. It can be used separately or in conjunction with the [FibeRoad™ System](#).

- ▶ Capacity of up to 24 splices
- ▶ Capacity of up to 12× SC / 24× LC connector
- ▶ PLC Splitter capability (small format)
- ▶ [FibeRoad™ System](#) compatible
- ▶ Hinged or stackable mounting
- ▶ Reserve space for cable slack in the bottom part of the tray
- ▶ Built-in patch cord management
- ▶ Patch cord cover
- ▶ Ability to change direction of the fiber storage
- ▶ Ability to place fibers in a secondary sheath (pigtail, ø 0.9 mm)
- ▶ Suitable for ribbon fibers



Fiber Optic Tray KM 5

TECHNICAL SPECIFICATIONS

Flammability Degree	V0
Material	PC / ABS
Color	light gray RAL 7035
Dimensions (H × W × D)	26 × 205 × 179 mm
Weight	0.2 kg

ORDERING CODES

85AV.94/0000F	KM 5 Kit for Heat Shrinkable Protection
85AV.94/00K2F	KM 5 Kit for Crimp Protection
85AV.94/00R3F	KM 5 Kit for Ribbon Protection
85C3.76/000X	KM 5 Kit for Heat Shrinkable Protection (for MDB boxes)
85C3.78/000X	KM 5 Kit for Crimp Protection (for MDB boxes)
85C3.77/000X	KM 5 Kit for Ribbon Protection (for MDB boxes)
493520	Heat Shrink Splice Protector (compatible with TS 12, 45 × 2.4 mm)



Fiber Optic Tray KM 5 (set)



KM 5 (FiberRoad™ System – cascade solution)



2x KM 5 (connected by a connecting piece)



KM 5 (with a lid and sticker)



KM 5 (FiberRoad™ System)



Connecting Piece KM 5



Splice Holder K 12 (for crimp splices)



Splice Holder RIB 3 (3x ribbon or splitter 4 x 4 mm)



Splice Holder TS 12 (for heat shrink splices)

More information: <https://www.micostelcom.com/en/fiber-optic-trays/fiber-optic-tray-km-5>